



AL1122 MPEG-4 Video & Audio Node



The M4VAN was designed with state of the art technology for video encoding and decoding. Using independent chip sets, the M4VAN uses DSP technology for both encoding and decoding with a co-processor for data flow and user control. While reducing cost, power consumption and heat, this platform allows for the development of future products with the capability of H.264 and resolution up to 1080p.

The M4VAN receives SD NTSC or PAL video and line-level audio and encodes the data using MPEG-4 and G.711 respectively. The M4VAN then packetizes this data into UDP/IP (Unicast or Multicast) packets and transmits this packet across an Ethernet network.

The M4VAN can be remotely operated via Apex, a web browser, telnet, or user created software. Logins are in the form of three different user levels: admin which allows changes to any setting; reader which allows only reading settings; and user which level is either admin or reader, depending on the user selection.

- 10 / 100 Mbps Ethernet connectivity
- TCP / IP, UDP / IP (Unicast and Multicast), ICMP, SMB, DHCP, ARP, and telnet protocols
- MPEG-4 baseline
- G.711 speech
- OS independent remote control
- APEX compatible
- Web browser (Mozilla Firefox 1.5+; Microsoft Internet Explorer 7) supported
- NNAT compatible
- User level access control

SPECIFICATIONS

DATA INPUT / OUTPUT

- NTSC and PAL Video Compatible
- Composite video - 75Ω BNC connector
- 1/8" audio jack - line level
- 10/100 Ethernet

ENCODING

- MPEG 4 baseline

POWER

- 2.5 mm circular jack
- Supply voltage (+10 VDC to +30 VDC)

MECHANICAL

- 6.5" L x 8.8" W x 1.5" H
- Approximately 2.0 lbs